



GENERAL NOTES:

- 1.) THE PERFORATED FACE OF THE PANEL IS MADE OF 22 GA. GALVANNEALED PERFORATED STEEL WITH 3/32" HOLES ON 1/8" STAGGERED CENTERS
- 2.) THE MOUNTING CLIPS ARE 11 GA. GALVANNEALED STEEL WITH PRE-DRILLED HOLES FOR EASY MOUNTING AND ARE DESIGNED TO SPACE THE PANELS 4" OFF THE FACE OF THE FINISHED WALL SURFACE
- 3.) PANEL FRAMING MEMBER IS ROLL FORMED 18 GA. GALVANNEALED STEEL CHANNEL
- 4.) ABSORPTIVE MATERIAL IS POLY-BAGGED FIBERGLASS ACOUSTIC FILL
- 5.) ENTIRE PANEL AND MOUNTING CLIPS ARE POWDER FINISHED IN CUSTOM COLOR SELECTED BY CUSTOMER
- 6.) WALL ANCHORS/MOUNTING FASTENERS ARE DETERMINED BY THE EXISTING WALL CONSTRUCTION

SOUND ABSORPTION COEFFICIENTS

OCTAVE BAND CENTER FREQUENCIES (Hz)	125	250	500	1K	2K	4K	NRC
"V" RIDGE ABSORPTION PANELS	0.46	0.86	1.36	1.20	1.03	0.03	1.10

*All testing conducted by Riverbank Acoustical Laboratories. Sound Absorption Coefficients by the Reverberation Room Method ASTM C-423-02/NVLA9 OR/P03

REVISIONS	DESCRIPTION	DATE	BY	DESCRIPTION	"V" RIDGE ABSORPTION PANEL	
		CUSTOMER			DRAWN BY	SCALE
				DATE	SHEET	NB-11-V

Noise Barriers, LLC
 1207 Remington Rd., Suite E
 Schaumburg, IL 60173
 Phone: (847) 843-0500
 Fax: (847) 843-0501
www.noisebarriers.com